

Product Information

Brand Panasonic
Type of product Air-conditioner
Model name CS-VZ12SKE/CU-VZ12SKE

Function (indicate if present)				If function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season 'Average'.			
Cooling	YES			Average (mandatory)	YES		
Heating	YES			Warmer (if designated)	NO		
				Colder (if designated)	NO		
Item	symbol	value	unit	Item	symbol	value	unit
Design load				Seasonal efficiency			
cooling	Pdesignc	3.50	kW	cooling	SEER	10.0	-
heating/Average	Pdesignh	4.20	kW	heating/Average	SCOP/A	5.9	-
heating/Warmer	Pdesignh	-	kW	heating/Warmer	SCOP/W	-	-
heating/Colder	Pdesignh	-	kW	heating/Colder	SCOP/C	-	-
Declared capacity (*) for cooling, at indoor temperature 27(19) °C and outdoor temperature Tj				Declared energy efficiency ratio (*), at indoor temperature 27(19) °C and outdoor temperature Tj			
Item	symbol	value	unit	Item	symbol	value	unit
Tj = 35°C	Pdc	3.50	kW	Tj = 35°C	EERd	4.88	-
Tj = 30°C	Pdc	2.58	kW	Tj = 30°C	EERd	7.44	-
Tj = 25°C	Pdc	1.66	kW	Tj = 25°C	EERd	12.34	-
Tj = 20°C	Pdc	1.10	kW	Tj = 20°C	EERd	20.29	-
Declared capacity (*) for heating/Average season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance (*)/Average season, at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7°C	Pdh	3.72	kW	Tj = -7°C	COPd	3.79	-
Tj = 2°C	Pdh	2.26	kW	Tj = 2°C	COPd	5.72	-
Tj = 7°C	Pdh	1.45	kW	Tj = 7°C	COPd	7.80	-
Tj = 12°C	Pdh	0.91	kW	Tj = 12°C	COPd	9.98	-
Tj = bivalent temperature	Pdh	4.20	kW	Tj = bivalent temperature	COPd	2.86	-
Tj = operating limit	Pdh	4.20	kW	Tj = operating limit	COPd	2.86	-
Declared capacity (*) for heating/Warmer season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance (*)/Warmer season, at indoor temperature 20 °C and outdoor temperature Tj			
Tj = 2°C	Pdh	-	kW	Tj = 2°C	COPd	-	-
Tj = 7°C	Pdh	-	kW	Tj = 7°C	COPd	-	-
Tj = 12°C	Pdh	-	kW	Tj = 12°C	COPd	-	-
Tj = bivalent temperature	Pdh	-	kW	Tj = bivalent temperature	COPd	-	-
Tj = operating limit	Pdh	-	kW	Tj = operating limit	COPd	-	-
Declared capacity (*) for heating/Colder season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance (*)/Colder season, at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7°C	Pdh	-	kW	Tj = -7°C	COPd	-	-
Tj = 2°C	Pdh	-	kW	Tj = 2°C	COPd	-	-
Tj = 7°C	Pdh	-	kW	Tj = 7°C	COPd	-	-
Tj = 12°C	Pdh	-	kW	Tj = 12°C	COPd	-	-
Tj = bivalent temperature	Pdh	-	kW	Tj = bivalent temperature	COPd	-	-
Tj = operating limit	Pdh	-	kW	Tj = operating limit	COPd	-	-
Tj = -15°C	Pdh	-	kW	Tj = -15°C	COPd	-	-

Function (indicate if present)				If function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season 'Average'.			
Cooling	YES			Average (mandatory)	YES		
Heating	YES			Warmer (if designated)	NO		
				Colder (if designated)	NO		
Item	symbol	value	unit	Item	symbol	value	unit
Bivalent temperature				Operating limit temperature			
heating/Average	Tbiv	-10	°C	heating/Average	Tol	-10	°C
heating/Warmer	Tbiv	-	°C	heating/Warmer	Tol	-	°C
heating/Colder	Tbiv	-	°C	heating/Colder	Tol	-	°C
Cycling interval capacity				Cycling interval efficiency			
for cooling	Pcycc	-	kW	for cooling	EERcyc	-	-
for heating	Pcyh	-	kW	for heating	COPcyc	-	-
Degradation co-efficient cooling(**)	Cdc	0.25	-	Degradation co-efficient heating(**)	Cdh	0.25	-
Electric power input in power modes other than 'active mode'				Annual electricity consumption			
off mode	P _{OFF}	1	W	cooling	Q _{CE}	122	kWh/a
standby mode	P _{SB}	1	W	heating/Average	Q _{HE}	995	kWh/a
thermostat-off mode	P _{TO}	23	W	heating/Warmer	Q _{HE}	-	kWh/a
crankcase heater mode	P _{CK}	0	W	heating/Colder	Q _{HE}	-	kWh/a
Capacity control (indicate one of three options)				Other Items			
fixed	NO			Sound power level (indoor/outdoor)	LWA	60 / 65	dB(A)
staged	NO			Global warming potential	GWP	675	kgCO ₂ eq.
variable	YES			Rated air flow (indoor/outdoor)	-	954 / 2124	m ³ /h
Contact details for obtaining more information	Name and address of the manufacturer or of its authorized representative. Panasonic Testing Centre, Panasonic Marketing Europe GmbH Winsbergring 15, 22525 Hamburg, Germany						
<p>(*) For staged capacity units, two values divided by a slash (/) will be declared in each box in the section 'Declared capacity of the unit' and 'declared EER/COP' of the unit.</p> <p>(**) If default Cd = 0,25 is chosen then (results from) cycling tests</p>							

GWP value is in accordance with Regulation (EU) No. 517/2014